

LDC1000XXWPR-G



SPECIFICATIONS

Type	LDC100029WPR-G	LDC100039WPR-G	LDC100062WPR-G	LDC1000104WPR-G
LED Type	SMD1415	SMD1921	SMD2727	
Pixel Pitch (mm)	2.97	3.91	6.25	10.4
Cabinet Size W x H (mm)	1000 x 1000 / 1000 x 500 / 1500 x 1000 / 1500 x 500			
Cabinet Depth (mm)	83			
Cabinet Weight (kg/m²)	22.5			
Module Size (mm)	500 x 250			
Module Resolution (px)	164 x 84 / 128 x 64 / 80 x 40 / 48 x 24			
Brightness (cd/m²)	5500		6500	
Refresh Rate (Hz)	3840			
Scan Rate	1 / 21	1 / 16	1 / 8	1 / 2
Gray Scale (bit)	16			
Power Consumption Max / Ave (W/m²)	600 / 200		780 / 200	
Viewing Angle H / V (deg)	160 / 160			
Cabinet Material	Aluminum			
Maintenance	Front and Rear			
AC Input Voltage (V)	90 - 264V			
Operating Temperature (°C)	-20 ~ 50			
IP Rating	IP65			
Certificates	CE(LVD, EMC), FCC, PSE, ETL, RoHs			

*All data provided are from factory lab and are subject to change without prior notice.