

I-TV COB Touch All In One



It's not just a display, it's a work of art.

The ultimate four-inone: power supply, receiving card, hub board and amplifier.



Effortless cross-device meetings with BYOM, regardless of screen type

- PC/mobile phone cloud conference, utilising AIO's function easily.
- No need to download cloud conferencing applications.







Wi-Fi 6



Bluetooth 5.3



Convenient and easy-to-use software, delivering simplicity and efficiency

- Visualised OSD menu, swift function switch.
- Small screen controls big screen, flexible control.



Scene Mode







Brightness



Input Source







Aspect Ratio



Led Configuration









I-TV COB TOUCH ALL IN ONE

Tailor-made for sound amplification in large conference rooms, immersive spatial audio

- Side seam sounding technology distributes sound evenly throughout venues.
- Multi-channel, multi-speaker to create surround sound.







Side seam sound

6-cavity 6-speaker

4x15W+2x30W





95dB

60Hz~20kHz



Powerful system capabilities and multiple interface configurations

- Supports dual system options to meet different requirements.
- Multi-layer video processing to achieve stunning multi-screen effects.
- · Multi-interface, easily creating professional conference solutions.











Android 13.0

Windows 10

HDMI IN*4

HDMI OUT*1











Audio in/out

Dual Wi-Fi screen mirroring, faster, more stable and secure

- Breaking network limitations, share screen anytime, anywhere. Automatically matching screencast code.
- Letting audience focus on the content without personal notifications popping up.








Auto

Matching



disturb





P₂P

Do not

SPECIFICATIONS

PRODUCT CODE	I-TV13815SFP	I-TV16519SFP	I-TV22012SFP	I-TV12013SFP	I-TV15017SFP	I-TV1802SFP
Size (inch)	138	165	220	120	150	180
Pixel Pitch (mm)	1.5	1.9	1.2	1.3	1.7	2.0
Overall Dimension (mm)	3080 × 1840 × 28 ¹	3690 × 2183 × 28 ¹	4910 × 2869 × 28 ¹	2694 × 1624 × 28 ¹	3360 × 1998 × 28 ¹	4026 × 2373 × 28 ¹
Net weight (kg)	122	172	296	87	131	185
Average power consumption (kw)	0.49	0.7	1.24	0.32	0.49	0.7
Maximum power consumption (kw)	1.45	2.05	3.65	0.94	1.45	2.05
Resolution	1920×1080	1920×1080	3840×2160	1920×1080	1920×1080	1920×1080
Contrast	6500:1					
Grayscale	13~16bit					
Speaker unit	4 full range units + 2 low frequency units					
Max. input power	120W					
Max. sound pressure level	95dB					
Frequency response	60Hz~20kHz					
Refresh Rate	3840Hz					
Brightness	100~600cd/m² (Adjustable)					
Viewing Angle (H/V)	160° / 140°					
Operating system	Android13.0, 8G + 64G, Cortex-A76 ×4 + Cortex-A55 ×4 Windows System (Optional)					
Cabinet material	Die-casting magnalium					
Installation method	Mobile Stand², Wall mounting, Ceiling-hanging					
Maintenance method	Front-maintenance					
Recommended viewing distance	≥3.2m	≥3.8m	≥2.4m	≥2.8m	≥3.4m	≥4m

^{1.} The thickness of screen



GET IN TOUCH

Phone: +61 1300 841 542 Email: sales@aurorasignage.com.au Website: www.aurorasignage.com.au

^{2.} The installation mode with mobile stand only available for 120", 138", 150", 165". Note: Specifications are for reference only and are subject to change without notice.